

# **BLANK PAGE**



IS 8672: 1989

## Indian Standard

''গুনটুছা ৭৪৪৪'' ''RE-AFFIRMLD 1994''

and the same of th

# PLIERS — FLAT NOSE WITHOUT CUTTER, SHORT — SPECIFICATION

(First Revision)

भारतीय मानक

चपटे ग्रग्रभाग बाले प्लास, कर्तक रहित, छोटे - विशिष्टि ( पहला पुनरीक्षण )

UDC 621.881.4

© BIS 1990

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

#### **FOREWORD**

This Indian Standard (First Revision) was adopted by the Bureau of Indian Standards on 6 December 1989 after the draft finalized by the Assembly Hand Tools Sectional Committee had been approved by the Production Engineering Division Council.

This Indian Standard was first issued in 1977. This revision has been taken up in order to align the standard with the work done at the international level and to give the latest references of revised standards. Dimensions have also been aligned with the international practices.

Flat nose pliers without cutter and with long nose are not covered in this standard. These have separately been covered in IS 3552: 1989.

While preparing this standard, details have been taken from ISO 5745-1982 'Pliers and nippers — Pliers for gripping and manipulating — Dimensions', issued by the International Organization for Standardization (ISO).

### Indian Standard

## PLIERS — FLAT NOSE WITHOUT CUTTER, SHORT — SPECIFICATION

(First Revision)

#### 1 SCOPE

1.1 This standard covers the dimensions and other requirements of flat nose pliers without cutter having short nose.

#### 2 REFERENCES

2.1 The following Indian Standards are necessary adjunct to this standard:

IS No.

Title

IS 2615: 1989

Technical supply conditions for pliers, pincers and nippers (second revision)

IS 11526: 1986

Nomenclature for pliers, pincers

and nippers

#### 3 NOMENCLATURE

3.1 Nomenclature of the pliers shall be as given in IS 11525: 1986.

4 DIMENSIONS - See Table 1.

#### 5 GENERAL REQUIREMENTS


5.1 The material, manufacture, workmanship and finish, tests, preservation and packing and sampling shall conform to IS 2615: 1989.

#### 6 HARDNESS

**6.1** The hardness of jaws shall be 350 to 550 HV (  $\approx$  36 to 52 HRC).

Table 1 Dimensions for Flat Nose Pliers Without Cutter - Short

All dimensions in millimetres.



				-			
Nominal Size	L	Tol on L	L <sub>3</sub>	Tol on $L_3$	$W_3$	$W_4$	$T_1$
125	125	± 6	25	0 -5	16	3.2	8
140	140	± 7	32	0 -6·3	18	4	.9
160	160	± 8	<b>4</b> 0	08	20	5	10

#### 7 TESTS

7.0 In addition to the tests specified in IS 2615: 1989, the tests laid down in 7.1 to 7.3 shall also be carried out.

7.1 Bend Test — The pliers when tested by bending a hard-drawn steel wire of 1.25 mm diameter shall work satisfactorily and shall not show any sign of damage or indentation on the nose on completion of the test.

7.2 Torsion Test — The pliers shall be tested for the requirements as laid down in 9.4 of IS 2615: 1989. The testing torque to be employed shall be as given in Table 2.

7.3 Handle Load Test -- The pliers shall be tested for permanent set as given in 9.5 of 1S 2615:

1989. The load to be employed shall be as given in Table 2 and the permanent set shall not exceed the values given in Table 2.

#### **8 DESIGNATION**

8.1 A flat nose plier without cutter, short of nominal size 140 mm shall be designated as:

Plier Short 140 — IS 8672


#### 9 MARKING

9.1 The pliers shall be clearly and legibly stamped with the nominal size and indication of the source of manufacture. The year of manufacture may also be marked if required by the purchaser.

Table 2 Test Requirements for Flat Nose Pliers Without Cutter, Short

( Clauses 7.2 and 7.3 )

All dimensions in millimetres.



L	l L,	Torsion Test		Load Test	
		Torque T Nm	Twist Max	Load (F)	Permanent Set
125	6 <b>3</b>	3	± 15°	630	1
140	71	3.5	± 15°	710	1
160	80	4.5	± 15•	800	1
	125 1 <b>4</b> 0	125 63 140 71	125 63 3 140 71 3·5	Torque     Twist $T$ Nm $Max$ $\alpha^{\circ}$ 125     63     3 $\pm$ 15°       140     71     3·5 $\pm$ 15°	Torque     Twist     Load (F) $T$ Nm $Max$ $\alpha^{\circ}$ 125     63     3 $\pm$ 15°     630       140     71     3·5 $\pm$ 15°     710

NOTE –  $S = W_1 - W_0$  ( see IS 2615: 3989)

#### Standard Mark

The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

#### Bureau of Indian Standards

BIS is a statutory institution established under the Bureau of Indian Standards Act, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

#### Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

#### Revision of Indian Standards

Indian Standards are reviewed periodically and revised, when necessary and amendments, it any, are issued from time to time. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition. Comments on this Indian Standard may be sent to BIS giving the following reference:

Doc: No. PE 05 (4825)

#### Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected	

#### BUREAU OF INDIAN STANDARDS

#### Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Mara, New Delhi 110002 Telephones: 331 01 31, 331 13 75

Telegrams: Manaksanstha
(Common to all Offices)

( Common to all Offices )
Regional Offices:

Central: Manak Bhavan, 9 Bahadur Shah Zafar Marg
NEW DELHI 110002

(331 01 31
331 13 75

Eastern: 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola CALCUTTA-700054 37 86 62

Northern: SCO 445-446, Sector 35-C, CHANDIGARH 160036

2 18 43

Southern: C. I. T. Campus, IV Cross Road, MADRAS 600113

41 29 16

Western: Manakalaya, E9 MIDC, Marol, Andheri (East) BOMBAY 400093

6 32 92 95

Branches: AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR.

COIMBATORE, FARIDABAD, GHAZIABAD, GUWAHATI, HYDERABAD, JAIPUR, KANPUR, PATNA, TRIVANDRUM.

Printed at Printograph, Delhi, India